

CASE NO.: AM9-99-0138

Serial No.: 09/487,502

September 19, 2006

Page 2

PATENT
Filed: January 19, 2000

ORIGINAL COPY

1. (currently amended) A computer-implemented method for digitally signing data, comprising:

generating a lattice \mathcal{L} having at least one short basis establishing a private key and at least one long basis establishing a public key;

mapping at least the message μ or a concatenation thereof to a message point "x" in n-dimensional space using a function "f" rendering infeasible the possibility of mapping two messages together in the space; and

using the short basis, finding a lattice point "y" of the lattice \mathcal{L} that is close to the message point "x" and

using at least the message point "x" and lattice point "y", digitally signing an entity, wherein the function "f" maps the message μ to a point on a grid and is collision intractable.
2. (canceled).
3. (currently amended) The method of Claim [[2]] 1, further comprising randomizing the function "f".
4. (original) The method of Claim 3, wherein the function "f" is randomized by concatenating the message μ with a random number p .
- 5, 6. (canceled).

1053-T3.AMZ

CASE NO.: AM9-99-0138
Serial No.: 09/487,502
September 19, 2006
Page 3

PATENT
Filed: January 19, 2000

NOT AVAILABLE COPY

7. (currently amended) The method of Claim [[6]] 1, wherein the collision intractability of the function "f" is derived from the hardness of lattice problems.
8. (canceled).
9. (original) The method of Claim 1, wherein the function "f" maps at least the message to a point on an auxiliary lattice.
10. (original) The method of Claim 1, further comprising verifying a digital signature at least in part by determining whether a difference between the lattice point "y" and the message point "x" is no more than a predetermined distance.
11. (original) The method of Claim 10, wherein the predetermined distance is related to the number of dimensions in the lattice \mathcal{L} .
12. (previously presented) A computer program storage device including a program of instructions for generating a digital signature for a message, the program of instructions including:

1053-73, AM2

CASE NO.: AM9-99-0138

Serial No.: 09/487,502

September 19, 2006

Page 4

PATENT

Filed: January 19, 2000

BEST AVAILABLE COPY

computer readable code means for mapping a message μ or a concatenation thereof to a message point "x" in n-dimensional space, the message point "x" being a point of a grid or a point of an auxiliary lattice;

computer readable code means for finding a point "y" of a key lattice \mathcal{L} that is not the same as the auxiliary lattice; and

computer readable code means for establishing a digital signature, based at least on the points "x" and "y".

13. (original) The computer program storage device of Claim 12, wherein the means for mapping uses a function "f" rendering infeasible the possibility of mapping two messages close together in the space, and wherein the means for finding includes using a hard to find short basis of the key lattice \mathcal{L} .

14. (original) The computer program storage device of Claim 13, further comprising means for randomizing the function "f".

15. (original) The computer program storage device of Claim 14, wherein the function "f" is randomized by concatenating the message μ with a random number ρ .

1053-73.AM2

CASE NO.: AM9-99-0138
Serial No.: 09/487,502
September 19, 2006
Page 5

PATENT
Filed: January 19, 2000

16. (original) The computer program storage device of Claim 12, wherein the function "f" maps the message μ to a point on a grid, and wherein the function "f" is collision intractable, the collision intractability being derived from the hardness of lattice problems.

17. (original) The computer program storage device of Claim 12, wherein the function "f" is not collision intractable.

18. (original) The computer program storage device of Claim 13, wherein the function "f" maps at least the message to a point on an auxiliary lattice.

19. (previously presented) A computer system for generating a digital signature of a message μ , comprising:

at least one sender computer including logic for executing method steps including:

mapping the message μ to a message point "x" at which it is not feasible to map any other message;

finding a lattice point "y"; and

transmitting at least the message μ and the points "x" and "y";

at least one receiver computer receiving the message μ and points "x" and "y" and including logic for executing method steps including:

1053-73.AM2

CASE NO.: AM9-99-0138

Serial No.: 09/487,502

September 19, 2006

Page 6

PATENT
Filed: January 19, 2000

BEST AVAILABLE COPY

determining whether a distance between the points "x" and "y" is related in a predetermined way to a predetermined distance, and based thereon determining whether the message μ has been properly signed.

20. (original) The system of Claim 19, wherein the mapping act is undertaken using a function "f" that maps the message point "x" to a point of a grid or of an auxiliary lattice, and further wherein the lattice point "y" is a member of a lattice \mathcal{L} , and the finding act is undertaken using a hard-to-find short basis of the lattice \mathcal{L} .

21. (original) The system of Claim 20, wherein the acts undertaken by the logic of the sender computer further comprise randomizing the function "f" by concatenating the message μ with a random number p.

22. (original) The system of Claim 20, wherein the function "f" is collision intractable.

23. (original) The system of Claim 22, wherein the collision intractability of the function "f" is derived from the hardness of lattice problems.

24. (original) The system of Claim 20, wherein the function "f" is not collision intractable.

1053-73.AM2

CASE NO.: AM9-99-0138
Serial No.: 09/487,502
September 19, 2006
Page 7

PATENT
Filed: January 19, 2000

SEE AMENDED CO.

25. (original) The system of Claim 20, wherein the predetermined distance is related to the number "r" of dimensions in the lattice \mathcal{L} .

26. (currently amended) A computer-implemented method for digitally signing data, comprising:
generating a lattice \mathcal{L} having at least one short basis and at least one long basis;
mapping at least the message μ or a concatenation thereof to a message point "x" in n-dimensional space, the message point "x" being an element of a set of spaced-apart points not on the lattice; and
using the short basis, finding a lattice point "y" of the lattice \mathcal{L} ; and
using at least the message point "x" and lattice point "y", digitally signing an entity, wherein the mapping is undertaken using a function "f" that is not collision intractable.

27 (canceled).

28. (currently amended) The method of Claim 2[[7]]6, further comprising randomizing the function "f" by concatenating the message μ with a random number ρ .

29. (currently amended) The method of Claim 2[[7]]6, wherein the function "f" maps the message μ to a point on a grid.

1053-73.AM2

CASE NO.: AM9-99-0138

Serial No.: 09/487,502

September 19, 2006

Page 8

PATENT

Filed: January 19, 2000

Original Filed in Japan 0007

30-32. (canceled)

33. (currently amended) The method of Claim 2[[7]]6, wherein the function "f" maps at least the message to a point on an auxiliary lattice.

34. (original) The method of Claim 26, further comprising verifying a digital signature at least in part by determining whether a difference between the lattice point "y" and the message point "x" is no more than a predetermined distance.

35. (original) The method of Claim 34, wherein the predetermined distance is related to the number of dimensions in the lattice \mathcal{L} .

1053-73.AM2